

Wiring, Printed - Component

[See General Information for Wiring, Printed - Component](#)

CEMEBO S R O

E203416

PORICI 1602/24

OBCHODNI USEK

678 01 BLANSKO, CZECH REPUBLIC

Type	Cond Width		Cond	SS/ DS	Max		Max		Flame	Meets	C	
	Min	Edge			Area	Solder	Oper	UL796				T
	mm(in)	mm(in)			Thk	Diam	Limits	Temp				Class
Multilayer printed wiring boards.												
ML	0.06 (0.002)	0.08 (0.003)	17.1 (0.67) Int: 68.6	DS	25.2 (1.0)	280	10	130	V-0	All	*	
ML-1	0.06 (0.002)	0.08 (0.003)	17.1 (0.67) Int: 34.3	DS	25.4 (1.0)	280	10	130	V-0	All	*	
Single layer printed wiring boards.												
1	0.18 (0.007)	0.15 (0.006)	18 (0.71)	DS	13 (0.5)	280	10	130	V-0	All	*	

* - - CTI/ PLC may be marked on individual board.

Marking: Company name and type designation. May be followed by a suffix to denote factory identification.

Last Updated on 2009-05-05

[Questions?](#)

[Notice of Disclaimer](#)

[Page Top](#)

Copyright © 2010 Underwriters Laboratories Inc.®

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2010 Underwriters Laboratories Inc.®"

An independent organization working for a safer world with integrity, precision and knowledge.

